

Data sheets

Universal Tentex FR + ws

Article number: 4418 / 77
Material: 100% PES
Weight: ca. 200 g/m²

Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

Specialities:

heat set ca. 185°C (> 185°C shrinkage ca. 1%)

Applications:

inflatables
banners
tents
sun umbrellas

Remarks:

New: recommended by Vutek for Fusion solvent DyeSub

universell printable with dyesub direct, dyesub transfer,
solvent and UV inks

front: coated for solvent & UV

* special size for HP Latex printers
back: open fabric + dyesubdirect coating

ATTENTION: In dyesub printing ink can migrate into the
coating and cause uncontrolled, time delayed colour changes

Product compatibilities:


Universal Tentex FR + ws is compatible to the following printers (print-method):

Vutek FabriVu (Sub Oil)	D-Gen Teleios (Sub water)
Gandi Jeti 3312 DS (Sub Oil)	Vutek UltraVu 33xx / 53xx (Solvent)
HP Scitex Pressjet (Solvent)	Vutek QS Series (UV curable)
NUR salsa ultima (Solvent)	Durst Rho 160/350 (UV curable)
NUR Fresco HIQ (Solvent)	Dupont Artistri (Sub water)
Mimaki JV 4 / TX2 sub direct (Sub water)	HP Expedio 3200 / 5000 (UV curable)
HP-Scitex XL Jet 2 / 3 / 5 (Solvent)	Océ Arizona (Solvent)
Mimaki JV 3 (eco solvent)	Paper Transfer (Sub Paper)
HP 10000s series (eco solvent)	Spühl Virtu (UV curable)
Gandi Aquajet (sub water)	Vutek 3360 Fusion (Sub sol)
ATP Color/Roland (Sub water)	Hollanders Colorbooster (Sub water)

Data sheets

Universal Tentex FR + ws

Product image:



www.bergertextil.com

++ 49 2151 65231-0

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may be subject to be changed without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.